

FOOTFALL DS⁶⁵ standard

Quality commercial underlay for heavy contract installations.
Made from a high content of post-consumer vehicle tyre waste.

SPECIFICATION

Characteristic	Test Method	Result
Nominal thickness		6.50mm
Roll length		11.00m
Roll width		1.37m
M ² per roll		15.07m ²
Weight M ²		ca.2.58kg/m ²
Nominal roll weight		ca.39kgs
End use specification	BS EN 14499: 2015	HC/U Heavy Contract Use
Work of compression	BS 4098: 1975	98J/m ²
Retention of work of compression	BS 4098: 1975	100%
Compression after dynamic loading	BS 4098: 1975	2.5mm
Loss in thickness after static loading	ISO 3416	2.9%
Loss in thickness after dynamic loading	ISO 2094	1.5%
Breaking strength - length	EN ISO 13934-1 ^a	489N
Breaking strength - width	EN ISO 13934-1 ^a	392N
Extension under force - length	EN ISO 13934-1	0.7%
Extension under force - width	EN ISO 13934-1	0.9%
Resistance to cracking	BS EN 14499: 2015	Pass
Resistance to bacteria		Biocide agent added
Flammability - Hot metal nut test	BS 4790: 1987	Low radius of effects of ignition
Tog rating	BS 4745: 2005	1.1
Impact sound improvement	BS EN ISO 10140-3: 2010	30dB

Concern for the future of our planet drives our business. Every Footfall product is made from recycled materials and is itself recyclable.

Footfall Flooring Ltd. | footfalluk.co.uk

FOOTFALL for the future