

FOOTFALL DS⁹⁰ comfort

Luxury commercial crumb underlay designed for heavy contract installations.
Made from a high content of post-consumer vehicle tyre waste.

SPECIFICATION

Characteristic	Test Method	Result
Nominal thickness		9.00mm
Roll length		8.00m
Roll width		1.37m
M ² per roll		10.96m ²
Weight M ²		ca.3.60kg/m ²
Nominal roll weight		ca.40kgs
End use specification	BS EN 14499: 2015	LU Luxury Contract Use
Work of compression	BS 4098: 1975	157J/m ²
Retention of work of compression	BS 4098: 1975	94%
Compression after dynamic loading	BS 4098: 1975	4.5mm
Loss in thickness after static loading	ISO 3416	1.9%
Loss in thickness after dynamic loading	ISO 2094	1.9%
Breaking strength - length	EN ISO 13934-1 ^a	429N
Breaking strength - width	EN ISO 13934-1 ^a	200N
Extension under force - length	EN ISO 13934-1	1.3%
Extension under force - width	EN ISO 13934-1	1.6%
Resistance to cracking	BS EN 14499: 2015	Pass
Resistance to bacteria		Biocide agent added
Flammability - Hot metal nut test	BS 4790: 1987	Low radius of effects of ignition
Tog rating	BS 4745: 2005	1.7
Impact sound improvement	BS EN ISO 10140-3: 2010	33dB

Concern for the future of our planet drives our business. Every Footfall product is made from recycled materials and is itself recyclable.

Footfall Flooring Ltd. | footfalluk.co.uk

FOOTFALL for the future