



Luxury residential carpet underlay.

Made from recycled PET bottle waste and post-consumer vehicle tyre waste.

SPECIFICATION

Characteristic	Test Method	Result
Nominal thickness		11.00mm
Roll length		7.30m
Roll width		1.37m
M ² per roll		10.00m ²
Weight M ²		ca.3.6kg/m ²
Nominal roll weight		ca.36kgs
End use specification	BS EN 14499: 2015	L/U Luxury Domestic Use
Work of compression	BS 4098: 1975	149J/m ²
Retention of work of compression	BS 4098: 1975	82%
Compression after dynamic loading	BS 4098: 1975	4.8mm
Loss in thickness after static loading	ISO 3416	17.4%
Loss in thickness after dynamic loading	ISO 2094	8%
Breaking strength - length	EN ISO 13934-1 ^a	236N
Breaking strength - width	EN ISO 13934-1 ^a	346N
Extension under force - length	EN ISO 13934-1	6%
Extension under force - width	EN ISO 13934-1	3.2%
Resistance to cracking	BS EN 14499: 2015	Pass
Flammability - Hot metal nut test	BS 4790: 1987	Low radius of effects of ignition
Tog rating	BS 4745: 2005	2.55
Impact sound improvement	BS EN ISO 10140-3: 2010	34dB

Concern for the future of our planet drives our business. Every Footfall product is made from recycled materials and is itself recyclable.

Footfall Flooring Ltd. | footfalluk.co.uk

FOOTFALL for the future