



Luxury residential carpet underlay.
Made from a high content of post-consumer vehicle tyre waste.

SPECIFICATION

Characteristic	Test Method	Result
Nominal thickness		8.00mm
Roll length		8.00m
Roll width		1.37m
M ² per roll		10.96m ²
Weight M ²		ca.3.10kg/m ²
Nominal roll weight		ca.34kgs
End use specification	BS EN 14499: 2015	HC/U Heavy Contract Use
Work of compression	BS 4098: 1975	109J/m ²
Retention of work of compression	BS 4098: 1975	94%
Compression after dynamic loading	BS 4098: 1975	3.1mm
Loss in thickness after static loading	ISO 3416	5.8%
Loss in thickness after dynamic loading	ISO 2094	4.1%
Breaking strength - length	EN ISO 13934-1 ^a	126N
Breaking strength - width	EN ISO 13934-1 ^a	97N
Extension under force - length	EN ISO 13934-1	5%
Extension under force - width	EN ISO 13934-1	1.5%
Resistance to cracking	BS EN 14499: 2015	Pass
Resistance to bacteria		Biocide agent added
Flammability - Hot metal nut test	BS 4790: 1987	Low radius of effects of ignition
Tog rating	BS 4745: 2005	1.4
Impact sound improvement	BS EN ISO 10140-3: 2010	33dB

Concern for the future of our planet drives our business. Every Footfall product is made from recycled materials and is itself recyclable.

Footfall Flooring Ltd. | footfalluk.co.uk

FOOTFALL for the future